

THOMSON  DELPHION		RESEARCH My Account Products	PRODUCTS Search: Quick/Number Boolean Advanced	INSIDE DELPHION
--	--	--	--	------------------------

The Delphion Integrated View


Get Now: ☒ PDF | [More choices...](#)


Tools: Add to Work File: [Create new Wor](#)

View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent...](#)

 [Ema](#)

 Title: **JP10289708A2: NONAQUEOUS ELECTROLYTE SECONDARY BATT
MANUFACTURE OF ELECTRODE PLATES OF THE SAME**

 Country: JP Japan

 Kind: A


 Inventor: MURAI TETSUYA;
TSUKAMOTO HISASHI;


 Assignee: JAPAN STORAGE BATTERY CO LTD
[News, Profiles, Stocks and More about this company](#)

 Published / Filed: 1998-10-27 / 1997-04-11

 Application JP1997000094026

Number:

 IPC Code: [H01M 4/02](#); [H01M 4/04](#); [H01M 10/40](#);

 Priority Number: 1997-04-11 JP1997000094026


 Abstract:


PROBLEM TO BE SOLVED: To provide a nonaqueous electrolyte secondary battery which can spread lithium on an entire electrode body uniformly as much as possible and enables large quantification, and a manufacturing method of its electrode plates.

SOLUTION: A lithium foil laminated film 50 which holds a metallic lithium foil 52 on a base film 51 is piled on a negative electrode plate 20 and pressurized with passing through between a pair of transcription rolls 53. After pressurization, the base film 51 is peeled off and the negative electrode plate 20, wherein very thin metallic lithium foil 52 is transcribed on the surface of electrode mix 23, is produced. The negative electrode plate 20 is wound together with a positive electrode plate, placing a separator between them to form an electrode body.

COPYRIGHT: (C)1998,JPO

 Family: None

 Other Abstract Info: CHEMABS 129(25)333313V CAN129(25)333313V DERABS C99-020193
DERC99-020193



[Nominate](#)

[this for the Gallery...](#)

THOMSON
DELPHION

RESEARCH


PRODUCTS

INSIDE DELPHION

My Account | Products

Search: Quick/Number Boolean Advanced

The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)Tools: Add to Work File: [Create new Wor](#)View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent...](#) [Ema](#)

Title: JP10289708A2: NONAQUEOUS ELECTROLYTE SECONDARY BATT
MANUFACTURE OF ELECTRODE PLATES OF THE SAME

Country: JP Japan

Kind: A

Inventor: MURAI TETSUYA;
TSUKAMOTO HISASHI;

Assignee: JAPAN STORAGE BATTERY CO LTD
[News, Profiles, Stocks and More about this company](#)

Published / Filed: 1998-10-27 / 1997-04-11

Application JP1997000094026

Number:

IPC Code: H01M 4/02; H01M 4/04; H01M 10/40;

Priority Number: 1997-04-11 JP1997000094026

Abstract:


... PROBLEM TO BE SOLVED: To provide a nonaqueous electrolyte secondary battery which can spread lithium on an entire electrode body uniformly as much as possible and enables large quantification, and a manufacturing method of its electrode plates.

... SOLUTION: A lithium foil laminated film 50 which holds a metallic lithium foil 52 on a base film 51 is piled on a negative electrode plate 20 and pressurized with passing through between a pair of transcription rolls 53. After pressurization, the base film 51 is peeled off and the negative electrode plate 20, wherein very thin metallic lithium foil 52 is transcribed on the surface of electrode mix 23, is produced. The negative electrode plate 20 is wound together with a positive electrode plate, placing a separator between them to form an electrode body.

... COPYRIGHT: (C)1998,JPO

Family: None

Other Abstract CHEMABS 129(25)333313V CAN129(25)333313V DERABS C99-020193
Info: DERC99-020193



[Nominate](#)

[this for the Gallery...](#)



(19)

(11) Publication number: **10**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **09094026**(51) Intl. Cl.: **H01M 4/02 H01M 4/04 H01M**(22) Application date: **11.04.97**

(30) Priority:	(71) Applicant: JAPAN STORAGE BAT LTD
(43) Date of application publication: 27.10.98	(72) Inventor: MURAI TETSUYA TSUKAMOTO HISASHI
(84) Designated contracting states:	(74) Representative:

(54) NONAQUEOUS ELECTROLYTE SECONDARY BATTERY AND MANUFACTURE OF ELECTRODE PLATES OF THE SAME


(57) Abstract:

PROBLEM TO BE SOLVED: To provide a nonaqueous electrolyte secondary battery which can spread lithium on an entire electrode body uniformly as much as possible and enables large quantification, and a manufacturing method of its electrode plates.

SOLUTION: A lithium foil laminated film 50 which holds a metallic lithium foil 52 on a base film 51 is piled on a negative electrode plate 20 and pressurized with passing through between a pair of transcription rolls 53. After pressurization, the base film 51 is peeled off and the negative electrode plate 20, wherein very thin metallic lithium foil 52 is transcribed on the surface of electrode mix 23, is

produced. The negative electrode plate 20 is wound together with a positive electrode plate, placing a separator between them to form an electrode body.

COPYRIGHT: (C)1998,JPO





(19)

(11) Publication number: **10**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **09094026**(51) Intl. Cl.: **H01M 4/02 H01M 4/04 H01M**(22) Application date: **11.04.97**

<p>(30) Priority:</p> <p>(43) Date of application publication: 27.10.98</p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: JAPAN STORAGE BAT LTD</p> <p>(72) Inventor: MURAI TETSUYA TSUKAMOTO HISASHI</p> <p>(74) Representative:</p>
---	--

**(54) NONAQUEOUS
ELECTROLYTE
SECONDARY BATTERY
AND MANUFACTURE OF
ELECTRODE PLATES OF
THE SAME**

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a nonaqueous electrolyte secondary battery which can spread lithium on an entire electrode body uniformly as much as possible and enables large quantification, and a manufacturing method of its electrode plates.

SOLUTION: A lithium foil laminated film 50 which holds a metallic lithium foil 52 on a base film 51 is piled on a negative electrode plate 20 and pressurized with passing through between a pair of transcription rolls 53. After pressurization, the base film 51 is peeled off and the negative electrode plate 20, wherein very thin metallic lithium foil 52 is transcribed on the surface of electrode mix 23, is

produced. The negative electrode plate 20 is wound together with a positive electrode plate, placing a separator between them to form an electrode body.

COPYRIGHT: (C)1998,JPO.

